| Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2014 | |
|---|---------|
| Име или търговска марка на доставчика | Candy |
| Product name / Commercial code | CVMA60B |
| Annual Energy Consumption, AEChood (kWh/a) | 37 |
| Energy Efficiency class (2010/30/EC) | Α |
| Energy Efficiency Index, EEI | 49.1 |
| Fluid Dynamic Efficiency (FDEhood) | 30,7 |
| Fluid Dynamic Efficiency class | Α |
| Lighting Efficiency (Lehood) | 24 |
| Lighting Efficiency class | В |
| Grease Filtering Efficiency | 68,2 |
| Grease Filtering Efficiency class | D |
| Air flow at Min/Max speed in normal use, Qmin/Qmax (m3/h) | 498 |
| Air flow at at intensive or boost setting (m3/h) | 612 |
| Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A)) | 62 |
| Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A)) | 66 |
| Power consumption in off mode (Po) (W) | 0,27 |
| Power consumption in standby mode (Ps) (W) | |
| Time increase factor, f | 0.9 |
| Measured air flow rate at best efficiency point, QBEP (m3/h) | 323 |
| Measured air pressure at best efficiency point, PBEP (Pa) | 363 |
| Measured electric power input at best efficiency point, WBEP (W) | 106 |
| Nominal power of the lighting system, WL (W) | 3 |
| Average illumination of the lighting system on the cooking surface, Emiddle (lux) | 86 |