

Identifikační značka modelu

FIDCP X625 L

Název nebo ochranná známka dodavatele	Candy
[M] Built-in / Free standing	Vestavný
Product Line	Trouba
Čistá váha (kg)	27,2
Index energetické účinnosti pro každ pečící prostor (EEIcavity) (%)_1	81.0
Index energetické účinnosti pro každ pečící prostor (EEIcavity) (%)_2	
Třída energetické účinnosti pro hlavní pečící prostor	A+
Třída energetické účinnosti pro druhý pečící prostor	
Energy consumption conventional (kWh) - cavity 1	0.98
Spotřeba energie v režimu s přirozenou konvekcí pro druhý pečící prostor (kWh)	
Spotřeba energie v režimu s nucenou konvekcí pro hlavní pečící prostor (kWh)	0.68
Spotřeba energie v režimu s nucenou konvekcí pro druhý pečící prostor (kWh)	
Počet pečících prostorů	1
Zdroje tepla pro jednotlivé pečící prostory	Elektrická
Heat source(s) - cavity 2	-
Objem jednotlivých pečících prostorů (l)_1	70
Objem jednotlivých pečících prostorů (l)_2	

Product information for networked equipment as per Regulation (EU) n° 801/2013

Identifikační značka modelu

FIDCP X625 L

Spotřeba energie v režimu stand-by (W)	1
Standby power management delay [min]	0
Off mode power consumption [W]	0
Off mode power management delay [min]	0
Spotřeba energie networku v režimu stand-by mode (W)	0
Networked standby power management delay [min]	0
Networked standby power consumption with all wired network ports connected and all wireless network ports activated [W]	0
How to activate wireless network port	-
How to deactivate wireless network port	-