Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2014

Tarnija nimi või kaubamärk

Candy

| Product name / Commercial code | CBT625/2W/1 |
|---|-------------|
| Annual Energy Consumption, AEChood (kWh/a) | 27,1 |
| Energy Efficiency class (2010/30/EC) | В |
| Energy Efficiency Index, EEI | 64.2 |
| Fluid Dynamic Efficiency (FDEhood) | 14,1 |
| Fluid Dynamic Efficiency class | D |
| Lighting Efficiency (Lehood) | 44,5 |
| Lighting Efficiency class | Α |
| Grease Filtering Efficiency | 74,9 |
| Grease Filtering Efficiency class | D |
| Air flow at Min/Max speed in normal use, Qmin/Qmax (m3/h) | 332 |
| Air flow at at intensive or boost setting (m3/h) | |
| Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A)) | 64 |
| Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A)) | |
| Power consumption in off mode (Po) (W) | 0 |
| Power consumption in standby mode (Ps) (W) | |
| Time increase factor, f | 1.5 |
| Measured air flow rate at best efficiency point, QBEP (m3/h) | 159 |
| Measured air pressure at best efficiency point, PBEP (Pa) | 150 |
| Measured electric power input at best efficiency point, WBEP (W) | 46,9 |
| Nominal power of the lighting system, WL (W) | 2 |
| Average illumination of the lighting system on the cooking surface, Emiddle (lux) | 89 |