

A szállító neve vagy védjegye Candy

| | |
|---|---------|
| Product name / Commercial code | CVMA90N |
| Annual Energy Consumption, AEC _{hood} (kWh/a) | 37 |
| Energoefektivitātes klase - no (2010/30/EC) | A |
| Energoefektivitātes indekss, EEI | 49.1 |
| Fluid Dynamic Efficiency (FDE _{hood}) | 30,7 |
| Fluid Dynamic Efficiency class | A |
| Lighting Efficiency (Le _{hood}) | 18,7 |
| Lighting Efficiency class | C |
| Grease Filtering Efficiency | 68,2 |
| Grease Filtering Efficiency class | D |
| Air flow at Min/Max speed in normal use, Q _{min} /Q _{max} (m ³ /h) | 498 |
| Air flow at at intensive or boost setting (m ³ /h) | 612 |
| Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A)) | 62 |
| Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A)) | 66 |
| Power consumption in off mode (P _o) (W) | 0,27 |
| Power consumption in standby mode (P _s) (W) | |
| Time increase factor, f | 0.9 |
| Measured air flow rate at best efficiency point, QBEP (m ³ /h) | 323 |
| Measured air pressure at best efficiency point, PBEP (Pa) | 363 |
| Measured electric power input at best efficiency point, WBEP (W) | 106 |
| Nominal power of the lighting system, WL (W) | 3 |
| Average illumination of the lighting system on the cooking surface, E _{middle} (lux) | 86 |