Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2014

Product name / Commercial code	
r rouder name / Commercial Code	CBT6130/3X
Annual Energy Consumption, AEChood (kWh/a)	26,4
Energy Efficiency class (2010/30/EC)	В
Energy Efficiency Index, EEI	63.6
Fluid Dynamic Efficiency (FDEhood)	14,4
Fluid Dynamic Efficiency class	D
Lighting Efficiency (Lehood)	35,5
Lighting Efficiency class	Α
Grease Filtering Efficiency	58,8
Grease Filtering Efficiency class	E
Air flow at Min/Max speed in normal use, Qmin/Qmax (m3/h)	329
Air flow at at intensive or boost setting (m3/h)	
Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A))	64
Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A))	
Power consumption in off mode (Po) (W)	0
Power consumption in standby mode (Ps) (W)	
Time increase factor, f	1.5
Measured air flow rate at best efficiency point, QBEP (m3/h)	157,8
Measured air pressure at best efficiency point, PBEP (Pa)	150
Measured electric power input at best efficiency point, WBEP (W)	45,6
Nominal power of the lighting system, WL (W)	2

71

Average illumination of the lighting system on the cooking surface, Emiddle (lux)