Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2	2014

Naam of handelsmerk leverancier	Candy
Product name / Commercial code	CFT610/5S/1
Annual Energy Consumption, AEChood (kWh/a)	43,6
Energy Efficiency class (2010/30/EC)	С
Energy Efficiency Index, EEI	81.5
Fluid Dynamic Efficiency (FDEhood)	9,5
Fluid Dynamic Efficiency class	E
Lighting Efficiency (Lehood)	41,5
Lighting Efficiency class	A
Grease Filtering Efficiency	80,8
Grease Filtering Efficiency class	С
Air flow at Min/Max speed in normal use, Qmin/Qmax (m3/h)	209
Air flow at at intensive or boost setting (m3/h)	
Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A))	71
Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A))	
Power consumption in off mode (Po) (W)	0
Power consumption in standby mode (Ps) (W)	
Time increase factor, f	1.7
Measured air flow rate at best efficiency point, QBEP (m3/h)	88,4
Measured air pressure at best efficiency point, PBEP (Pa)	262
Measured electric power input at best efficiency point, WBEP (W)	67,9
Nominal power of the lighting system, WL (W)	2
Average illumination of the lighting system on the cooking surface, Emiddle (lux)	108