Naam of handelsmerk leverancier	Haier
Product name / Commercial code	HATS6CBS6BVOC
Annual Energy Consumption, AEChood (kWh/a)	45,1
Energy Efficiency class (2010/30/EC)	Α
Energy Efficiency Index, EEI	A
Fluid Dynamic Efficiency (FDEhood)	34,3
Fluid Dynamic Efficiency class	Α
Lighting Efficiency (Lehood)	68,1
Lighting Efficiency class	Α
Grease Filtering Efficiency	75,1
Grease Filtering Efficiency class	С
Air flow at Min/Max speed in normal use, Qmin/Qmax (m3/h)	395
Air flow at at intensive or boost setting (m3/h)	720
Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A))	55
Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A))	68
Power consumption in off mode (Po) (W)	0
Power consumption in standby mode (Ps) (W)	0,49
Time increase factor, f	0,9
Measured air flow rate at best efficiency point, QBEP (m3/h)	385
Measured air pressure at best efficiency point, PBEP (Pa)	415
Measured electric power input at best efficiency point, WBEP (W)	142
Nominal power of the lighting system, WL (W)	7
Average illumination of the lighting system on the cooking surface, Emiddle (lux)	477