



## **WALL-MOUNTED**

HCE160X/1

✓ Led light

MAIN FEATURES	
Model	HCE160X/1
Product code	36901761
EAN Code	8016361974173
Manufacturer	Candy Hoover Group S.r.l.
Installation type	Wall-mounted
Typology	Integrated

TECHNICAL FEATURES	
Connectivity	None
Frequency (Hz)	50
IoT App	None
Grease filter type	Multilayer cassette
Total power of the lamps (W)	2
Type of control	Mechanical push button
Number of motors	1

Voltage (V)       220-240         PROGRAMMES AND FUNCTIONS         Boost position       No         Number of speed settings       3         AESTHETIC         Colour       Stainless Steel         Material body       Stainless steel         PERFORMANCE         Min./Max. extraction rate (m3/hr)       510         Energy Efficiency class (2010/30/EC)       C         Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A))       66         Power (W)       <1000 W         DIMENSIONS       ***         Product height (mm)       1080         Height of product without chimney (mm)       40         Width of the product (mm)       500         Full product depth (mm)       500         Full product depth (mm)       570         Packaged Product Height (mm)       570         Width of the packed product (mm)       570         Packaged Product Depth(mm)       660         Diameter of air outlet (mm)       150         Net weight (kg)       8,9	Type of lamps used	LED
Boost position         No           Number of speed settings         3           AESTHETIC           Colour         Stainless Steel           PERFORMANCE           Min./Max. extraction rate (m3/hr)         510           Energy Efficiency class (2010/30/EC)         C           Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A))         66           Power (W)         <1000 W	Voltage (V)	220-240
AESTHETIC         Colour       Stainless Steel         Material body       Stainless steel         PERFORMANCE         Min./Max. extraction rate (m3/hr)       510         Energy Efficiency class (2010/30/EC)       C         Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A))       66         Power (W)       <1000 W	PROGRAMMES AND FUNCTIONS	
AESTHETIC  Colour Stainless Steel  Material body Stainless steel  PERFORMANCE  Min./Max. extraction rate (m3/hr) 510  Energy Efficiency class (2010/30/EC) C  Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A))  Power (W) <1000 W  DIMENSIONS  Product height (mm) 1080  Height of product without chimney (mm) 40  Width of the product (mm) 500  Full product depth (mm) 500  Packaged Product Height (mm) 570  Width of the packed product (mm) 570  Packaged Product Depth (mm) 660  Diameter of air outlet (mm) 150	Boost position	No
Colour Stainless Steel  Material body Stainless steel  PERFORMANCE  Min./Max. extraction rate (m3/hr) 510  Energy Efficiency class (2010/30/EC) C  Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A))  Power (W) <1000 W  DIMENSIONS  Product height (mm) 1080  Height of product without chimney (mm) 40  Width of the product (mm) 500  Full product depth (mm) 500  Packaged Product Height (mm) 570  Packaged Product Depth(mm) 660  Diameter of air outlet (mm) 150	Number of speed settings	3
Material body       Stainless steel         PERFORMANCE         Min./Max. extraction rate (m3/hr)       510         Energy Efficiency class (2010/30/EC)       C         Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A))       66         Power (W)       <1000 W	AESTHETIC	
PERFORMANCE         Min./Max. extraction rate (m3/hr)       510         Energy Efficiency class (2010/30/EC)       C         Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A))       66         Power (W)       <1000 W	Colour	Stainless Steel
Min./Max. extraction rate (m3/hr)       510         Energy Efficiency class (2010/30/EC)       C         Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A))       66         Power (W)       <1000 W	Material body	Stainless steel
Energy Efficiency class (2010/30/EC) C Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A))  Power (W) <1000 W  DIMENSIONS  Product height (mm) 1080  Height of product without chimney (mm) 40  Width of the product (mm) 500  Full product depth (mm) 500  Packaged Product Height (mm) 570  Width of the packed product (mm) 570  Packaged Product Depth(mm) 660  Diameter of air outlet (mm) 150	PERFORMANCE	
Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A))  Power (W) <1000 W  DIMENSIONS  Product height (mm) 1080  Height of product without chimney (mm) 40  Width of the product (mm) 500  Full product depth (mm) 500  Packaged Product Height (mm) 570  Width of the packed product (mm) 570  Packaged Product Depth(mm) 660  Diameter of air outlet (mm) 150	Min./Max. extraction rate (m3/hr)	510
emissions at Min/Max speed available in normal use (dB(A))  Power (W) <1000 W  DIMENSIONS  Product height (mm) 1080  Height of product without chimney (mm) 40  Width of the product (mm) 600  Full product depth (mm) 500  Packaged Product Height (mm) 370  Width of the packed product (mm) 570  Packaged Product Depth(mm) 660  Diameter of air outlet (mm) 150	Energy Efficiency class (2010/30/EC)	С
DIMENSIONSProduct height (mm)1080Height of product without chimney (mm)40Width of the product (mm)600Full product depth (mm)500Packaged Product Height (mm)370Width of the packed product (mm)570Packaged Product Depth(mm)660Diameter of air outlet (mm)150	emissions at Min/Max speed available in normal	66
Product height (mm) 1080  Height of product without chimney (mm) 40  Width of the product (mm) 600  Full product depth (mm) 500  Packaged Product Height (mm) 370  Width of the packed product (mm) 570  Packaged Product Depth(mm) 660  Diameter of air outlet (mm) 150	Power (W)	<1000 W
Height of product without chimney (mm)  Width of the product (mm)  Full product depth (mm)  Packaged Product Height (mm)  Width of the packed product (mm)  Fackaged Product Depth(mm)  Diameter of air outlet (mm)  150	DIMENSIONS	
Width of the product (mm) 600 Full product depth (mm) 500 Packaged Product Height (mm) 370 Width of the packed product (mm) 570 Packaged Product Depth(mm) 660 Diameter of air outlet (mm) 150	Product height (mm)	1080
Full product depth (mm) 500 Packaged Product Height (mm) 370 Width of the packed product (mm) 570 Packaged Product Depth(mm) 660 Diameter of air outlet (mm) 150	Height of product without chimney (mm)	40
Packaged Product Height (mm) 370  Width of the packed product (mm) 570  Packaged Product Depth(mm) 660  Diameter of air outlet (mm) 150	Width of the product (mm)	600
Width of the packed product (mm) 570 Packaged Product Depth(mm) 660 Diameter of air outlet (mm) 150	Full product depth (mm)	500
Packaged Product Depth(mm) 660  Diameter of air outlet (mm) 150	Packaged Product Height (mm)	370
Diameter of air outlet (mm)	Width of the packed product (mm)	570
	Packaged Product Depth(mm)	660
Net weight (kg) 8.9	Diameter of air outlet (mm)	150
	Net weight (kg)	8.9

Gross weight (kg)